## 3300 ANSI LUMENS • TRUE XGA • MULTIMEDIA PROJECTOR

# PLC-XP41/L

XGA Portable Multimedia Projector



#### **IMPRESSIVE 3300 ANSI LUMENS OF BRIGHTNESS**

A 275W NSH lamp combined with Sanyo's new optical system delivers an impressive 3300 ANSI lumens of brightness.

#### INTELLIGENT DIGITAL SHARPNESS CONTROL

This high-performance image processing technology analyzes the incoming signal and controls the sharpness of picture data only, while text and other elements that are already sharp are left unprocessed.

#### ECO MODE FOR INCREASED LAMP LIFE

The PLC-XP41/L features a new Eco mode which switches the lamp ballast power from 275 watts to 220 watts, increasing lamp life while decreasing the brightness level approximately 20%.

#### **3D DIGITAL PROGRESSIVE CIRCUIT**

3D sampling for each pixel along with SANYO's unique movement detection algorithm program lead to increased vertical and diagonal resolution on moving video images.

#### NETWORK CONNECTIVITY

Sanyo's new optional PJ-Net Organizer system allows for operation and administration of a projector via a network. Presentations can be run, projector status can be checked, and projector functions can be controlled through a web browser. An alarm and notification can be automatically sent via E-mail whenever the projector encounters a problem, allowing the administrator to act quickly to resolve the issue.

#### HDTV COMPATIBLE

The SANYO PLC XP41/L is High Definition Television Compatible, accepting the 1080i, 1035i, 720p, 575p, 575i, 480p and 480i HDTV resolution standards.

#### DIGITAL KEYSTONE CORRECTION

SANYO's new X-Y digital keystone correction feature compensates for angled projector placement by digitally altering the pixels to produce undistorted images both horizontally and vertically.

#### WHISPER QUIET FAN

The PLC-XP41/L employs a new Whisper Quiet fan producing an amazingly low noise level of only 35 dBA (Eco mode).



PRESENTATION TECHNOLOGIES 21605 Plummer Street Chatsworth, CA 91311 Ph: 818.998.7322 ext. 288 Fax 818.717.2719 www.sanyolcd.com

### Specifications

Desclution	
Resolution	XGA (1024 x 768)
Brightness (typical)	3300 ANSI Lumens
Uniformity	90%
LCD Panel System	1.3" TET Poly x 3
Number of Pixels	2,359,296 (786,432 x 3)
Contrast Ratio	550:1 (tull on/ott)
Projection Image (diagonal)	31″-400″
Aspect Ratio	4:3
Throw Distance	4.6'-47'
Zoom/Focus	Powered (1:1.3 zoom)
Up/Down Ratio	10:0 – 1:1
Digital Keystone Correction	Vert. +/- 40°, Horiz. +/- 10°
Projection System	Polarized Beam Splitter optical system
Projection Lens	F1.8-2.1 / f1.9"-2.5"
Lens Throw Ratio	1.82.4:1
Projection Lamp	275W NSH
Scanning Frequency	H 15-100kHz; V 50-100Hz (auto sense/select)
Dot Clock	160 MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NNTSC4.43
Computer Compatibility	SXGA, <b>XGA</b> , SVGA, VGA
Sound Output	I wopiece stereo 2W rms
Voltage	100-240V AC; 50/60/Hz (auto sense/select)
BTU Rating	1297
dB Rating	35.0 (Eco mode)
Power Consumption	380W
Dimensions (WxHxD)	12.6" x6.6"x16.9"
Net Weight	PLC-XP41: 17.4 lbs.; PLC -XP41L: 15.0 lbs.
User Maintenance	Clean air filters, replace lamp assembly
Input Terminal Panel 1	1 D-Sub 15 • 1 DVI • 1 audio (stereo mini jack)
Input Terminal Panel 2	5 BNC (RGBHV) or 3BNC (Video/Y, Cb/Pb, Cr/Pr)
	• 1 audio (stereo mini jack)
Input Terminal Panel 3	3 RCA (Video/Y, Cb/Pb, Cr/Pr)
input forminal function	● 2 RCA Audio (L & R) ● 1 S-Video
Additional Input Terminals	1 Wired remote control jack (stereo mini jack)
	● 1 USB ●1 Control Port (Mini Din 8-pin)
Included Accessories	Wired/Wireless I/R Remote Control w/Mouse Pad
	and Laser Pointer   AC power cord  VGA Cable
	Wired remote cable      PS/2, Serial, MAC Control
	Cables   MAC/VGA Adapter  Dust cover
	• Lens cover      • Owner's manual
Ontional Accessories	Optional Lenses (see below)
Optional Accessories Warranty	Three years parts and labor; 90 days lamp;
wanany	Quick Repair Program under warranty
	Quick Repair Flogran under warding

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

**Optional Lens Specifications** On-Axis Short Long Short Zoom Zoom Fixed LNS Part NS-W32 LNS-W31A No. T31A Zoom No Powe Power Throv 0.8: 25 - 1.83-4.2Ratio F Stop 2.6 2.0 - 2.92.5 – 3.1 Lenath 9.25 7.6 8.5 Weight 3.5 lbs 3.7 lbs 4.2 lbs 211 dog include 2



Optional PJ-Net Organizer Model# POA - PN01